


Wassar 360 / Wassar 550

自動洗衣機 Automatic Washing Machine

Wassar 360L

自動洗衣脫水機 Automatic Washing Extractor



- 大直徑內膽設計，特別適用於對牛仔，休閒服，風雨衣等厚料衣物進行石洗和酵洗
- 前置式結構，水比小，配合變頻調速，滿足多種洗滌要求，降低洗衣成本
- 機身可傾斜，自動卸料
- 採用PLC可編程控制器控制及人性化操作界面觸摸顯示屏操作，可記憶多種洗衣程式及多個步驟
- 採用蒸汽直接加熱，即時/到溫計時選擇
- 本機標配一套電控氣動入水系統，配合流量計可準確控制水位(另可選購一套電控氣動入水系統)
- 配有手動加藥系統
- Wassar 360、Wassar 550不帶脫水功能，用戶可選購本公司NS-2500系列工業脫水機配合使用
- Wassar 360L具有自動預脫水功能，極大地節省人力並顯著地提高生產效率

選購件：

鹽水配量缸連輸送系統-200L
藥水配量缸-100L
自動入藥水系統-100L
外置式間接熱交換器系統
另增氣動排水系統 - Ø8"
電控氣動入水系統
VaporTec 200 納米霧化系統
循環運水泵連過濾系統


- Large diameter of inner drum, especially suitable for stone wash and enzyme wash of thick garment such as jeans, casual wear, coat, etc.
- Front loading structure, lower water ratio, and variable frequency speed control can satisfy the requirements of various washes with lower cost
- Tiltable machine body for automatic garment unloading
- Adopt PLC and human friendly touch screen for operation; it can memorize many groups of programs and steps
- Heating directly by steam; users can select immediate or up-to temperature timing
- With one set of electric controlled pneumatic water feeding system as standard configuration in conjunction with flowmeter for accurate water level control(additional one set of electric controlled pneumatic water feeding system can be purchased optionally)
- With manual chemical feeding system
- Wassar 360 and Wassar 550 without extracting function. Users could purchase NS-2500 series industrial extractor for this purpose
- Wassar 360L with automatic pre-spinning function, labor saving and high efficiency

Options:

Salt dosing tank with feeding system -200L
Chemical dosing tank-100L
Automatic chemical feeding system-100L
External indirect heat exchange system
Optional pneumatic water draining system - Ø8"
Electric Controlled Pneumatic Water Feeding System
VaporTec 200
Water circulation pump with filtering system



Wassar 360L 皮帶輪驅動系統
Pulley driving system of Wassar 360L





Wassar 360/550 齒輪驅動系統
Gear driving system of Wassar 360/550



觸摸顯示屏
Touch screen



可傾斜卸料系統
Tilting system for garment unloading



Wassar 360
機身尺寸圖 Machine Size(mm)

選購件Options:



O-I-21-04-200
鹽水配量缸連輸送系統-200L
Salt dosing tank with
feeding system-200L




O-I-21-03-100
藥水配量缸-100L
Chemical dosing tank-100L



O-I-21-02-100
自動入藥水系統-100L
Automatic Chemical Feeding
System-100L



O-I-82-01
另增氣動排水系統 - Ø8"
Optional pneumatic water
draining system - Ø8"




O-I-04-3-1
電控氣動入水系統 - Ø3"
Electric Controlled Pneumatic
Water Feeding System - Ø3"



O-I-52-05 適用於 For WASSAR 360
O-I-52-06 適用於 For WASSAR 550
外置式間接加熱系統
External indirect heating system



VaporTec 200
納米霧化系統



外置式間接加熱系統示意圖
Diagram of External indirect heating system

型號 Model	容量(kg) Capacity	內膽容積(m³) Inner Drum Volume	電源 Power Supply	馬達功率(kW) Motor Power	內膽尺寸(mm) Inner Drum Size	外膽尺寸(mm) Outer Drum Size	脫水速度(RPM) Extracting Speed	洗滌速度(RPM) Washing Speed	機身尺寸(mm) Machine Size
Wassar 360	360	3.6	3PH/380V/50Hz	18.5	Ø1810x1450x4	Ø1910x1715x3	-	12~38	2950x3400x2500
Wassar 360L	360	3.6		30	Ø1810x1450x4	Ø1910x1715x3	150		2950x3400x3000*
Wassar 550	500	5		18.5	Ø1980x1640x4	Ø2085x1905x3	-		3200x3210x2620



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下
G/F., 52 Wing Hong St.,
Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078 E-MAIL: info@ngaishing.com
Fax: (852) 2785 3149 Http://www.ngaishing.com